

## 1250 KVA DIESEL GENERATOR

### FEATURES & BENEFITS

- Maximum 1400 kVA, 380V, 1500 RPM
- Constant voltage AVR (Automatic Voltage Regulator)
- 24 Volt Electric Starter
- 1000 Litre Fuel Tank, 6 Hours @ 75% load
- Silent Version ( $\pm 80$ dBa)
- In-line, 4 stroke, water-cooled, Turbo charged with aftercooler
- Three Phase Output
- DeepSea DSE6120 Digital Control Panel
- Low oil pressure system
- Low water cut out engine protection



 **Baudouin**

| GENERAL DATA                   |             |
|--------------------------------|-------------|
| <b>Model:</b>                  | BPD1250S3-B |
| <b>Prime Power (P.R.P):</b>    | 1250 kVA    |
| <b>Stand-by Power (L.T.P):</b> | 1400 kVA    |
| <b>Amps:</b>                   | 2127 A      |
| <b>Power Factor / COS:</b>     | 0.8         |
| <b>Frequency:</b>              | 50 Hz       |
| <b>Voltage:</b>                | 380 V       |
| <b>Phases:</b>                 | Three Phase |
| <b>Engine Speed:</b>           | 1500 RPM    |
| <b>Length:</b>                 | 6058 mm     |
| <b>Width:</b>                  | 2438 mm     |
| <b>Height:</b>                 | 2591 mm     |
| <b>Weight:</b>                 | 13100 kg's  |
| <b>Tank Capacity:</b>          | 1000 l      |

| ADDITIONAL                     |                      |
|--------------------------------|----------------------|
| <b>Running Time:</b>           | 6 Hours @ 75% load   |
| <b>Structure Type:</b>         | Silent               |
| <b>Noise Level (7m):</b>       | 80 dBA               |
| <b>Auto Voltage Regulator:</b> | Constant voltage AVR |
| <b>ISO9001 Certified:</b>      | Yes                  |
| <b>CE Certified:</b>           | Yes                  |
| <b>Fuel Cons. @ 100% Load:</b> | 217.6                |
| <b>Fuel Cons. @ 75% Load:</b>  | 160.3                |
| <b>Fuel Cons. @ 50% Load:</b>  | 108.9                |

| ENGINE DATA                  |                                                                 |
|------------------------------|-----------------------------------------------------------------|
| <b>Brand:</b>                | Baudouin                                                        |
| <b>Model:</b>                | 12M33G1400/5                                                    |
| <b>Type:</b>                 | In-line, 4 stroke, water-cooled, Turbo charged with aftercooler |
| <b>Starting System:</b>      | 24 Volt Electric Starter                                        |
| <b>Auto-Decompression:</b>   | Yes                                                             |
| <b>Cubic Capacity (l):</b>   | 39.2                                                            |
| <b>Compression Ratio:</b>    | 15:1                                                            |
| <b>Rated Power (kW/RPM):</b> | 1210 / 1500                                                     |
| <b>Fuel Type:</b>            | Diesel                                                          |
| <b>Lube Oil:</b>             | 15W40                                                           |
| <b>Low Pressure Alert:</b>   | Yes                                                             |
| <b>Low Fuel Cut Out:</b>     | Yes                                                             |

| CONTROL PANEL               |                       |
|-----------------------------|-----------------------|
| <b>Model:</b>               | DeepSea DSE6120       |
| <b>Type:</b>                | Digital Control Panel |
| <b>Analogue Inputs:</b>     | 2                     |
| <b>Mains Phase Voltage:</b> | Yes                   |
| <b>Mains Line Voltage:</b>  | Yes                   |

| ALTERNATOR              |                 |
|-------------------------|-----------------|
| <b>Model:</b>           | DPC404H         |
| <b>Pole Number:</b>     | 4               |
| <b>Excitation Mode:</b> | Self Excitation |

**Johannesburg**  
011 397 7373

**Pietermaritzburg**  
033 007 0812

**Nelspruit**  
013 007 1753

**Bloemfontein**  
051 001 1429

[www.BunduPower.co.za](http://www.BunduPower.co.za)

\* Specs subject to change without prior notice. \* Measurements based on ISO8528-1 Standards \* All rating at Sea Level, 25°C Ambient Temp.

|                                                                                   |                                  |                 |
|-----------------------------------------------------------------------------------|----------------------------------|-----------------|
|  | Model : <b>12M33G1400/5</b>      | Date : 14/01/19 |
|                                                                                   | <b>PowerKit Engine Datasheet</b> | Page : 1 / 4    |

## Ratings

| RPM  | Gross Engine Output |         |
|------|---------------------|---------|
|      | PRP kWm             | ESP kWm |
| 1500 | 1100                | 1210    |

## Basic data

|                                                                 |                                 |
|-----------------------------------------------------------------|---------------------------------|
| Engine model                                                    | 12M33G1400/5                    |
| N° of Cylinders / Valves                                        | 12 / 48                         |
| Cylinders arrangement                                           | At Vee                          |
| Bore x Stroke (mm)                                              | 150 x 185                       |
| Displacement (L)                                                | 39.2                            |
| Thermodynamic Cycle                                             | Diesel 4 stroke                 |
| Cooling System                                                  | Liquid (water + 50% antifreeze) |
| Injection System                                                | Direct                          |
| Fuel System                                                     | Mechanical Pump                 |
| Aspiration                                                      | Turbocharged and Aftercooled    |
| Compression ratio                                               | 15 : 1                          |
| Flywheel housing                                                | SAE 0                           |
| Flywheel                                                        | 18"                             |
| N° of teeth on flywheel ring gear                               | 194                             |
| Inertia of flywheel (kg/m²)                                     | 7.14                            |
| Inertia of crankshaft (kg/m²)                                   | 3.34                            |
| Emission standard                                               | N/A                             |
| Overall Dimensions with radiator (Length x Width x Height) (mm) | 3440 x 1780 x 2380              |
| Engine dry weight (kg)                                          | 4240                            |
| Engine wet weight (includes oil, coolant) (kg)                  | 4580                            |

DPK-TDS-EN-12M33-0006-19-01-14 Moteurs Baudouin reserve the right to modify these specifications, without notice. Document not contractual.

|                                                                                   |                                  |                 |
|-----------------------------------------------------------------------------------|----------------------------------|-----------------|
|  | Model : <b>12M33G1400/5</b>      | Date : 14/01/19 |
|                                                                                   | <b>PowerKit Engine Datasheet</b> | Page : 2 / 4    |

## Air intake system

|                                                  |      |
|--------------------------------------------------|------|
| Air intake temperature rise (°C) .....           | ≤ 5  |
| Air intake restriction clean filter (mBar) ..... | ≤ 30 |
| Air intake restriction dirty filter (mBar) ..... | ≤ 65 |
| Recommended air flow @ PRP (m³/min) .....        | 77.7 |
| Recommended air flow @ ESP (m³/min) .....        | 83.5 |
| Min. diameter of intake pipe (mm) .....          | 140  |

## Intercooling system

|                                                                               |       |
|-------------------------------------------------------------------------------|-------|
| Intercooler heat dissipating capacity @ PRP (kJ/s) .....                      | 248.3 |
| Intercooler heat dissipating capacity @ ESP (kJ/s) .....                      | 278.5 |
| Max. intake temperature @ 25°C ambient temperature (°C) .....                 | 60    |
| Max. difference between intake temperature and ambient temperature (°C) ..... | ≤ 21  |
| Max. intake pressure drop of intercooler (mBar) .....                         | 120   |

## Cooling system with Made in EU radiator

|                                                                   |                                                               |
|-------------------------------------------------------------------|---------------------------------------------------------------|
| System designed for ambient temperature up to (°C) .....          | 50                                                            |
| Radiator type .....                                               | Electrical                                                    |
| Fan type .....                                                    | Electric driven pusher - 2 x 18.5 kWe 400 Vac 1450 Rpm motors |
| Min. inside diameter of coolant outlet pipe (mm) .....            | 84                                                            |
| Coolant capacity of radiator and pipes (L) .....                  | 105                                                           |
| Coolant alarm (shutdown) temperature (°C) .....                   | 103                                                           |
| Thermostat opening temperature / full open temperature (°C) ..... | 77 / 87                                                       |
| Min. pressure in cooling system (Bar) .....                       | 0.5                                                           |
| Coolant capacity of the engine (L) .....                          | 83                                                            |
| Cooling fan airflow (m³/min) .....                                | 1140                                                          |
| Max additional restriction - Duct allowance (Pa) .....            | 175                                                           |

## Exhaust system

|                                                           |       |
|-----------------------------------------------------------|-------|
| Max. exhaust back pressure (mBar) .....                   | 75    |
| Max. exhaust temperature before turbocharger (°C) .....   | ≤ 750 |
| Max. exhaust temperature after turbocharger (°C) .....    | ≤ 550 |
| Exhaust flow @ PRP (m³/min) .....                         | 218   |
| Exhaust flow @ ESP (m³/min) .....                         | 237   |
| Min. diameter of exhaust pipe (mm) .....                  | 200   |
| Max. bending moment of exhaust gas exit flange (Nm) ..... | 10    |

|                                                                                   |                                  |                 |
|-----------------------------------------------------------------------------------|----------------------------------|-----------------|
|  | Model : <b>12M33G1400/5</b>      | Date : 14/01/19 |
|                                                                                   | <b>PowerKit Engine Datasheet</b> | Page : 3 / 4    |

## Lubrication system

|                                                                  |               |
|------------------------------------------------------------------|---------------|
| Oil capacity Low / High (L)                                      | 117 / 155     |
| Oil pressure in normal condition idle speed (Bar)                | $\geq 2$      |
| Oil pressure in normal condition at 1500 Rpm @ PRP (Bar)         | 4 - 6.5       |
| Lowest oil pressure alarm (shutdown) (Bar)                       | 2             |
| Max. oil temperature (°C)                                        | 105           |
| Oil flow (L/min)                                                 | $\geq 392$    |
| Oil fuel consumption ratio based on engine fuel consumption data | $\leq 0.3 \%$ |
| Total system capacity (including filters) (L)                    | 160           |

## Noise

|                                                    |       |
|----------------------------------------------------|-------|
| Diesel engine noise (Acoustic power level) (dB(A)) | 121.6 |
|----------------------------------------------------|-------|

## Fuel system

|                                           |            |
|-------------------------------------------|------------|
| Governor                                  | Electronic |
| Max. restriction at fuel pump inlet (Bar) | 0.5        |
| Max. fuel return restriction (Bar)        | 0.5        |
| Max. fuel inlet temperature (°C)          | 70         |
| Fuel supply flow (L/hr)                   | 1070       |
| Min. pressure of fuel pump (Bar)          | 1.3        |
| Min. diameter of inlet pipe (mm)          | 14         |
| Min. diameter of return pipe (mm)         | 14         |

## Electrical system

|                                                                    |       |
|--------------------------------------------------------------------|-------|
| Electrical system voltage (negative to ground) (Vdc)               | 24    |
| Starter power (kW)                                                 | 10    |
| Battery charger current (A)                                        | 55    |
| Max. electric resistance of starting circuit ( $\Omega$ )          | 0.008 |
| Min. sectional area of wire (mm <sup>2</sup> )                     | 95    |
| Min. cold start temperature without auxiliary starting device (°C) | - 5   |
| Min. cold start temperature with auxiliary starting device (°C)    | - 10  |

|                                                                                   |                                  |                 |
|-----------------------------------------------------------------------------------|----------------------------------|-----------------|
|  | Model : <b>12M33G1400/5</b>      | Date : 14/01/19 |
|                                                                                   | <b>PowerKit Engine Datasheet</b> | Page : 4 / 4    |

## Heat balance test data (with ambient temperature 28 °C)

Total heat dissipation @ ESP (kJ/s) .....1800.9

## Performance data

Mean Piston Speed (m/s) .....9.25  
 BMEP (Bar) .....24.69  
 Fan absorbed power (kW) .....33

## Fuel consumption

| Rating                           | gr/kWh | L/hr  |
|----------------------------------|--------|-------|
| 100% ESP                         | 200.5  | 242.9 |
| 100% PRP                         | 197.5  | 217.6 |
| 75% PRP                          | 194.2  | 160.3 |
| 50% PRP                          | 197.3  | 108.9 |
| 25% PRP                          | 217.4  | 59.8  |
| Fuel consumption tolerance + 3 % |        |       |

## Ratings definitions

### Emergency Standby Power (ESP)

Emergency Standby Power is the maximum power available for a varying load for the duration of a main power network failure. The average load factor over 24 hours of operation should not exceed 70% of the engine's ESP power rating. Typical operational hours of the engine is 200 hours per year, with a maximum usage of 500 hours per year. This includes an annual maximum of 25 hours per year at the ESP power rating. No overload capability is allowed. The engine is not to be used for sustained utility paralleling applications.

### Prime Power (PRP)

Prime Power is the maximum power available for unlimited hours of usage in a variable load application. The average load factor should not exceed 70% of the engine's PRP power rating during any 24 hour period. An overload capability of 10% is available, however, this is limited to 1 hour within every 12 hour period.

- 1) All ratings are based on operating conditions under ISO 8528-1, ISO 3046, DIN6271. Performance tolerance of  $\pm 5\%$ .
- 2) Test conditions : 100 kPa, 25°C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L. Derating may be required for conditions outside these; please contact the factory for details.
- 3) Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.

# DSE6110/20 MKII

## AUTO START & AUTO MAINS FAILURE CONTROL MODULES

DSE6120 MKII



DSE6110 MKII



### KEY FEATURES

- Large back-lit text display
- Multiple display languages
- Heated display option available
- DSENet® expansion compatible
- Data logging facility
- Fully configurable via PC using USB communication
- Front panel configuration
- Efficient power save mode
- 3 phase generator sensing
- 3 phase mains (utility) sensing (DSE6120 MKII only)
- Generator/load power monitoring (kW, kV A, kV Ar, pf)
- Accumulated power monitoring (kW h, kVA h, kVAR h)
- Generator/load current monitoring and protection
- Generator overload protection (kW)
- Breaker control via fascia buttons
- Fuel and start outputs, configurable when using CAN
- 4 configurable DC outputs
- 4 configurable analogue/digital inputs
- Support for 0 to 10 V &

- 4 to 20 mA oil pressure sensors
- 6 configurable digital inputs
- Configurable staged loading outputs
- CAN, MPU and alternator speed sensing in one variant
- 3 engine maintenance alarms
- Engine speed protection
- Engine hours counter
- Engine pre-heat
- Engine run-time scheduler
- Engine idle control for starting & stopping
- Fuel pump control
- Real time clock
- Battery voltage monitoring
- Start on low battery voltage
- Configurable remote start input
- 1 alternative configuration
- Comprehensive warning, electrical trip or shutdown protection upon fault condition
- LCD and LED alarm indication
- Customisable information screens
- Configurable event log (100)
- Tier 4 ECO engine support including exhaust fluids & filters

- J1939-75 instrumentation output, configurable CAN instrumentation and alarms
- Start on low battery
- Enhanced alarm functionality
- Low load alarm

### KEY BENEFITS

- Automatically transfers between mains (utility) and generator (DSE6120 MKII only)
- Increased input and output expansion capability via DSENet®
- User-friendly set-up and button layout for ease of use
- Multiple parameters are monitored simultaneously which are clearly displayed on a large back-lit text display via multiple languages
- The module can be configured to suit a wide range of applications
- Uses DSE Configuration Suite PC Software for simplified configuration
- Licence-free PC software
- IP65 rating (with optional gasket) offers increased resistance to water ingress

### SPECIFICATIONS

#### DC SUPPLY

**CONTINUOUS VOLTAGE RATING**  
8 V to 35 V Continuous

#### CRANKING DROPOUTS

Able to survive 0 V for 50 mS, providing supply was at least 10 V before dropout and supply recovers to 5 V. This is achieved without the need for internal batteries. LEDs and backlight will not be maintained during cranking.

#### MAXIMUM OPERATING CURRENT

100 mA at 12 V, 105 mA at 24 V

#### MAXIMUM STANDBY CURRENT

60 mA at 12 V, 55 mA at 24 V

#### MAXIMUM SLEEP CURRENT

40 mA at 12 V, 35 mA at 24 V

#### GENERATOR & MAINS (UTILITY)

**VOLTAGE RANGE**  
15 V to 415 V AC (Ph to N)  
26 V to 719 V AC (Ph to Ph)

#### FREQUENCY RANGE

3.5 Hz to 75 Hz

#### INPUTS

**DIGITAL INPUTS A to F**  
Negative switching

#### ANALOGUE INPUT A

Configurable as:  
Negative switching digital input  
0 V to 10 V  
4 mA to 20 mA  
0 Ω to 240 Ω

#### ANALOGUE INPUTS B TO D

Configurable as:  
Negative switching digital input  
0 Ω to 480 Ω

#### OUTPUTS

##### OUTPUT A (FUEL)

10 A short term, 5 A continuous, at supply voltage

##### OUTPUT B (START)

10 A short term, 5 A continuous, at supply voltage

##### AUXILIARY OUTPUTS C, D, E & F

2 A DC at supply voltage

#### DIMENSIONS

**OVERALL**  
216 mm x 158 mm x 43 mm  
8.5" x 6.2" x 1.5"

#### PANEL CUT-OUT

184 mm x 137 mm  
7.2" x 5.3"

#### MAXIMUM PANEL THICKNESS

8 mm  
0.3"

#### STORAGE TEMPERATURE RANGE

-40 °C to +85 °C  
-40 °F to +185 °F

#### OPERATING TEMPERATURE RANGE

**NON HEATED DISPLAY VARIANT**  
-30 °C to +70 °C  
-22 °F to +158 °F

#### HEATED DISPLAY VARIANT

-40 °C to +70 °C  
-40 °F to +158 °F

### RELATED MATERIALS

#### TITLE

DSE6110/20 MKII Installation Instructions  
DSE6110/20 MKII Operator Manual  
DSE6110/20 MKII Configuration Suite PC Manual

#### PART NO.

053-173  
057-226  
057-224

### OPTIONAL PARTS

#### PART

IP65 Gasket

#### PART NUMBER

020-521

### DEEP SEA ELECTRONICS PLC UK

Highfield House, Hunmanby Industrial Estate, Hunmanby YO14 0PH  
**TELEPHONE** +44 (0) 1723 890099 **FACSIMILE** +44 (0) 1723 893303  
**EMAIL** sales@deepseapl.com **WEBSITE** www.deepseapl.com

### DEEP SEA ELECTRONICS INC USA

3230 Williams Avenue, Rockford, IL 61101-2668 USA  
**TELEPHONE** +1 (815) 316 8706 **FACSIMILE** +1 (815) 316 8708  
**EMAIL** sales@deepseausa.com **WEBSITE** www.deepseausa.com

# DSE6110/20 MKII

## AUTO START & AUTO MAINS FAILURE CONTROL MODULES

The DSE6110 MKII Auto Start Control Module and the DSE6120 MKII Auto Mains (Utility) Failure Control Module are suitable for a wide variety of single gen-set applications.

Monitoring engine speed, oil pressure, coolant temperature, frequency, voltage, current, power and fuel level, the modules give comprehensive engine and alternator protection. This is indicated on a large back-lit LCD text display via an array of warning, electrical trip and shutdown alarms in multiple languages.

Electronic J1939 (CAN) and non-electronic MPU and alternator sensing engine support for diesel, gas and petrol engines all in one variant. With a number of flexible inputs, outputs and protections, the modules can be easily adapted to suit a wide range of applications.

Through USB Communication both modules can be configured using the DSE Configuration Suite PC Software or through the module's front panel editor.

Using the DSE Configuration Suite PC Software the controller is easy to use and configure which allows alteration of operating parameters, sequences, timers and alarms.

### AVAILABLE VARIANTS

|         |                                         |
|---------|-----------------------------------------|
| 6110-03 | Auto Start with real time clock         |
| 6120-03 | Auto Mains Failure with real time clock |

### ENVIRONMENTAL TESTING STANDARDS

#### ELECTRO-MAGNETIC COMPATIBILITY

BS EN 61000-6-2  
EMC Generic Immunity Standard for the Industrial Environment  
BS EN 61000-6-4  
EMC Generic Emission Standard for the Industrial Environment

#### ELECTRICAL SAFETY

BS EN 60950  
Safety of Information Technology Equipment, including Electrical Business Equipment

#### TEMPERATURE

BS EN 60068-2-1  
Ab/Ae Cold Test -30 °C  
BS EN 60068-2-2  
Bb/Be Dry Heat +70 °C

#### VIBRATION

BS EN 60068-2-6  
Ten sweeps in each of three major axes  
5 Hz to 8 Hz at +/-7.5 mm,  
8 Hz to 500 Hz at 2 GN

#### HUMIDITY

BS EN 60068-2-30  
Db Damp Heat Cyclic 20/55 °C at 95% RH 48 Hours  
BS EN 60068-2-78  
Cab Damp Heat Static 40 °C at 93% RH 48 Hours

#### SHOCK

BS EN 60068-2-27  
Three shocks in each of three major axes  
15 GN in 11 mS

#### DEGREES OF PROTECTION PROVIDED BY ENCLOSURES

BS EN 60529  
IP65 - Front of module when installed into the control panel with the optional sealing gasket.

## COMPREHENSIVE FEATURE LIST TO SUIT A WIDE VARIETY OF GEN-SET APPLICATIONS

