BPD2500S3-B

2500 KVA DIESEL GENERATOR

FEATURES & BENEFITS

- Maximum 2750 kVA, 380V, 1500 RPM
- Constant voltage AVR (Automatic Voltage Regulator)
- 24 Volt Electric Starter
- 3500 Litre Fuel Tank, 10 Hours @ 75% load
- 40' Container Version (±85dBA)
- V-Type, 4 stroke, water-cooled, Turbo charged with aftercooler
- Three Phase Output
- DeepSea DSE6120 Digital Control Panel
- Low oil pressure system
- Low water cut out engine protection

GENERAL DATA	
Model:	BPD2500S3-B
Prime Power (P.R.P):	2500 kVA
Stand-by Power (L.T.P):	2750 kVA
Amps:	4178 A
Power Factor / COS:	0.8
Frequency:	50 Hz
Voltage:	380 V
Phases:	Three Phase
Engine Speed:	1500 RPM
Length:	12192 mm
Width:	2438 mm
Height:	2896 mm
Weight:	23000 kg's
Tank Capacity:	3500 l

ADDITIONAL	
Running Time:	10 Hours @ 75% load
Structure Type:	40' Container
Noise Level (7m):	85 dBA
Auto Voltage Regulator:	Constant voltage AVR
ISO9001 Certified:	Yes
CE Certified:	Yes
Fuel Cons. @ 100% Load:	466.9
Fuel Cons. @ 75% Load:	350
Fuel Cons. @ 50% Load:	235

ENGINE DATA	
Brand:	Baudouin
Model:	12M55G2750/5
Type:	V-Type, 4 stroke, water-cooled, Turbo charged with aftercooler
Starting System:	24 Volt Electric Starter
Auto-Decompression:	Yes
Cubic Capacity (l):	65.65
Compression Ratio:	16.5:1
Rated Power (kW/RPM):	2200 / 1500
Fuel Type:	Diesel
Lube Oil:	15W40
Low Pressure Alert:	Yes
Low Fuel Cut Out:	Yes

CONTROL PANEL	
Model:	DeepSea DSE6120
Type:	Digital Control Panel
Analogue Inputs:	2
Mains Phase Voltage:	Yes
Mains Line Voltage:	Yes

ALTERNATOR	
Model:	LSA 52.3 L12
Pole Number:	4
Excitation Mode:	Self Excitation

Maputo, Moçambique

+258 85 176 3143 comercial@cobalt.co.mz **www.cobalt.co.mz**

* Especificações sujeitas a alteração sem aviso prévio. * Medições baseadas nas normas ISO8528-1Todos os valores referem-se ao nível do mar, com temperatura ambiente de 25°C.

Ratings

RPM	Gross Engine Output	
	PRP kWm	ESP kWm
1500	2200 *	2450

Basic data

Engine model 12M55G2750/5
N° of Cylinders / Valves ..... 12 / 48
Cylinders arrangement ..... At Vee
Bore x Stroke (mm) ..... 180 x 215
Displacement (L) 65.65
Thermodynamic Cycle ..... Diesel 4 stroke
Cooling System ..... Liquid (water + 50% antifreeze)
Injection System ..... Direct
Fuel System ..... High Pressure Common Rail
Aspiration ..... Turbocharged and Aftercooled
Compression ratio ..... 16.5 : 1
Flywheel housing ..... SAE 00
Flywheel ..... 21"
N° of teeth on flywheel ring gear 202
Inertia of flywheel (kg/m²) 20.78
Inertia of crankshaft (kg/m²) 16.16
Emission standard ..... N/A
Overall Dimensions without radiator (Length x Width x Height) (mm) ..... 2934 x 1544 x 2654
Engine dry weight without radiator and without radiator pipes (kg) 9550
Engine dry weight with radiator and radiator pipes (kg) ..... TBA
Engine wet weight with radiator (includes oil, coolant) (kg) ..... TBA

* The indicated PRP Power is for reference only. This engine is designed for emergency standby power (ESP) applications only. Its use is limited to a maximum of 200 hours per year, including an annual maximum of 25 hours per year at the ESP rating.

DPK-TDS-EN-12M55-0004-19-05-31 Moteurs Baudouin reserve the right to modify these specifications, without notice. Document not contractual.

Air intake system

Air intake temperature rise (°C) ..... ≤ 5
Air intake restriction clean filter (mBar) ..... ≤ 30
Air intake restriction dirty filter (mBar) ..... ≤ 70
Recommended air flow @ PRP (m³/min) ..... N/A
Recommended air flow @ ESP (m³/min) 164.5
Min. diameter of intake pipe (mm) 250

Aftercooling system

Aftercooler system type ..... Air to Water
Aftercooler heat dissipating capacity @ PRP (kJ/s) ..... N/A
Aftercooler heat dissipating capacity @ ESP (kJ/s) 620
Max. intake temperature @ 25°C ambient temperature (°C) 55
Max. difference between intake temperature and ambient temperature (°C) ..... TBA
Max. intake pressure drop of aftercooler (mBar) 50

Cooling system without radiator

System designed for ambient temperature up to (°C) 50
Radiator type ..... Electrical
Fan type ..... Electric driven pusher - 4 x 30 kWe 400 Vac 1450 Rpm motors
Min. inside diameter of coolant outlet pipe (mm) 96
Coolant capacity of radiator and pipes (L) ..... TBA
Coolant alarm (shutdown) temperature (°C) 103
Thermostat opening temperature / full open temperature (°C) ..... 78 / 90
Min. pressure in cooling system (Bar) ..... TBA
Coolant capacity of the engine (L) 306
Cooling fan airflow (m³/min) ..... TBA
Max additional restriction - Duct allowance (Pa) ..... TBA

Exhaust system

Max. exhaust back pressure (mBar) 75
Max. exhaust temperature before turbocharger (°C) ..... ≤ 650
Max. exhaust temperature after turbocharger (°C) ..... TBA
Exhaust flow @ PRP (m³/min) ..... N/A
Exhaust flow @ ESP (m³/min) 500.1
Min. diameter of exhaust pipe (mm) 280
Max. bending moment of exhaust gas exit flange (Nm) ..... TBA

DPK-TDS-EN-12M55-0004-19-05-31 Moteurs Baudouin reserve the right to modify these specifications, without notice. Document not contractual.

Lubrication system

Oil capacity Low / High (L) ..... 380 / 480
Oil pressure in normal condition idle speed (Bar) ..... ≥ 2
Oil pressure in normal condition at 1500 Rpm @ PRP (Bar) ..... 4 - 5.5
Lowest oil pressure alarm (shutdown) (Bar) 2
Max. oil temperature (°C) 105
Oil flow (L/min) ..... ≥ 1300
Oil fuel consumption ratio based on engine fuel consumption data ..... ≤ 0.25 %
Total system capacity (including filters) (L) 560

Heat balance test data (with ambient temperature 28 °C)

Total heat dissipation @ ESP (kJ/s) 5555

Fuel system

Governor ..... ECU
Max. restriction at fuel pump inlet (Bar) 0.1
Max. fuel return restriction (Bar) 0.2
Max. fuel inlet temperature (°C) 70
Fuel supply flow (L/hr) 2800
Min. pressure of fuel pump (Bar) 0.5
Min. diameter of inlet pipe (mm) 25
Min. diameter of return pipe (mm) 25

Electrical system

Electrical system voltage (negative to ground) (Vdc) 24
Starter power (kW) ..... 2 x 8,5
Battery charger current (A) 55
Battery charger absorbed power (kW) 1.6
Max. electric resistance of starting circuit (Ω) 0.008
Min. sectional area of wire (mm²) ..... 2 x 95
Min. cold start temperature without auxiliary starting device (°C) [1] ..... -10
Min. cold start temperature with auxiliary starting device (°C) [1] ..... TBA

[1] Engines used in emergency standby application or application that require immediate start under load, must be equipped with coolant heaters. Baudouin recommend heaters installation to be executed by providing constant coolant circulation across all the engine components. Two heaters are required for V-type engines, one per each side.

DPK-TDS-EN-12M55-0004-19-05-31 Moteurs Baudouin reserve the right to modify these specifications, without notice. Document not contractual.

Performance data

Mean Piston Speed (m/s) 10.75

BMEP (Bar) 29.9

Fan absorbed power (kW) ..... TBA

Noise

Diesel engine noise (Acoustic power level) (dB(A)) 123.8

Noise - upper side (dB(A)) 107

Noise - right side (view from flywheel) (dB(A)) 106.2

Noise - left side (view from flywheel) (dB(A)) 106.3

Noise – front (radiator) side (dB(A)) 106.2

Noise – rear (flywheel) side (dB(A)) 105.4

Notes :

a) Noise test made at 100% of the ESP power, 1 mt. distance, on engine without radiator, without cooling fan and without silencer.

b) Noise test refers to GB/T 1859 norm : Reciprocating internal combustion engines. Measurement of emitted airborne noise. Engineering method and survey method

Fuel consumption

Rating	gr/kWh	L/hr
100% ESP	192.0	560
100% PRP	N/A	N/A
75% PRP	N/A	N/A
50% PRP	N/A	N/A
25% PRP	N/A	N/A
	Fuel consumption tolerance + 3 %	

Ratings definitions

Emergency Standby Power (ESP)

Emergency Standby Power is the maximum power available for a varying load for the duration of a main power network failure. The average load factor over 24 hours of operation should not exceed 70% of the engine's ESP power rating. Typical operational hours of the engine is 200 hours per year, with a maximum usage of 500 hours per year. This includes an annual maximum of 25 hours per year at the ESP power rating. No overload capability is allowed. The engine is not to be used for sustained utility paralleling applications.

Prime Power (PRP)

Prime Power is the maximum power available for unlimited hours of usage in a variable load application. The average load factor should not exceed 70% of the engine's PRP power rating during any 24 hour period. An overload capability of 10% is available, however, this is limited to 1 hour within every 12 hour period.

1) All ratings are based on operating conditions under ISO 8528-1, ISO 3046, DIN6271. Performance tolerance of ±5%.
2) Test conditions : 100 kPa, 25°C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L. Derating may be required for conditions outside these; please contact the factory for details.
3) Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.

DPK-TDS-EN-12M55-0004-19-05-31 Moteurs Baudouin reserve the right to modify these specifications, without notice. Document not contractual.

DSEGenset®

DSE6110/20 MKII

AUTO START & AUTO MAINS FAILURE CONTROL MODULES

DSE**6110 MKII**

DSE**6120 MKII**

KEY FEATURES

- Large back-lit text display
- Multiple display languages
- Heated display option available
- DSENet® expansion compatible
- Data logging facility
- Fully configurable via PC using USB communication
- Front panel configuration
- Efficient power save mode
- 3 phase generator sensing
- 3 phase mains (utility) sensing (DSE6120 MKII only)
- Generator/load power monitoring (kW, kV A, kV Ar, pf)
- Accumulated power monitoring (kW h, kVA h, kVAr h)
- Generator/load current monitoring and protection
- Generator overload protection (kW)
- Breaker control via fascia buttons
- Fuel and start outputs, configurable when using CAN
- 4 configurable DC outputs
- 4 configurable analogue/digital inputs
- Support for 0 to10 V & 4 to 20 mA oil pressure sensors
- 6 configurable digital inputs
- Configurable staged loading outputs
- CAN, MPU and alternator speed sensing in one variant
- 3 engine maintenance alarms
- Engine speed protection
- Engine hours counter
- Engine pre-heat
- Engine run-time scheduler
- Engine idle control for starting & stopping
- Fuel pump control
- Real time clock
- Battery voltage monitoring
- Start on low battery voltage
- Configurable remote start input
- 1 alternative configuration
- Comprehensive warning, electrical trip or shutdown protection upon fault condition
- LCD and LED alarm indication
- Customisable information screens
- Configurable event log (100)
- Tier 4 ECO engine support including exhaust fluids & filters
- J1939-75 instrumentation output, configurable CAN instrumentation and alarms
- Start on low battery
- Enhanced alarm functionality
- Low load alarm

KEY BENEFITS

- Automatically transfers between mains (utility) and generator (DSE6120 MKII only)
- Increased input and output expansion capability via DSENet®
- User-friendly set-up and button layout for ease of use
- Multiple parameters are monitored simultaneously which are clearly displayed on a large back-lit text display via multiple languages
- The module can be configured to suit a wide range of applications
- Uses DSE Configuration Suite PC Software for simplified configuration
- Licence-free PC software
- IP65 rating (with optional gasket) offers increased resistance to water ingress

RELATED MATERIALS

TITLE	PART NO.
DSE6110/20 MKII Installation Instructions	053-173
DSE6110/20 MKII Operator Manual	057-226
DSE6110/20 MKII Configuration Suite PC Manual	057-224

SPECIFICATIONS

DC SUPPLY

CONTINUOUS VOLTAGE RATING
8 V to 35 V Continuous

CRANKING DROPOUTS
Able to survive 0 V for 50 mS, providing supply was at least 10 V before dropout and supply recovers to 5 V. This is achieved without the need for internal batteries. LEDs and backlight will not be maintained during cranking.

MAXIMUM OPERATING CURRENT
100 mA at 12 V, 105 mA at 24 V

MAXIMUM STANDBY CURRENT
60 mA at 12 V, 55 mA at 24 V

MAXIMUM SLEEP CURRENT
40 mA at 12 V, 35 mA at 24 V

GENERATOR & MAINS (UTILITY)

VOLTAGE RANGE
15 V to 415 V AC (Ph to N)
26 V to 719 V AC (Ph to Ph)

FREQUENCY RANGE
3.5 Hz to 75 Hz

INPUTS

DIGITAL INPUTS A to F
Negative switching

ANALOGUE INPUT A
Configurable as:
Negative switching digital input
0 V to 10 V
4 mA to 20 mA
0 Ω to 240 Ω

ANALOGUE INPUTS B TO D
Configurable as:
Negative switching digital input
0 Ω to 480 Ω

OUTPUTS

OUTPUT A (FUEL)
10 A short term, 5 A continuous, at supply voltage

OUTPUT B (START)
10 A short term, 5 A continuous, at supply voltage

AUXILIARY OUTPUTS C, D, E & F
2 A DC at supply voltage

DIMENSIONS

OVERALL
216 mm x 158 mm x 43 mm
8.5'' x 6.2" x 1.5"

PANEL CUT-OUT
184 mm x 137 mm
7.2'' x 5.3"

MAXIMUM PANEL THICKNESS
8 mm
0.3"

STORAGE TEMPERATURE RANGE
-40 °C to +85 °C
-40 °F to +185 °F

OPERATING TEMPERATURE RANGE

NON HEATED DISPLAY VARIANT
-30°C to +70°C
-22 °F to +158 °F

HEATED DISPLAY VARIANT
-40 °C to +70 °C
-40 °F to +158 °F

OPTIONAL PARTS

PART	PART NUMBER
IP65 Gasket	020-521

DEEP SEA ELECTRONICS PLC UK
Highfield House, Hunmanby Industrial Estate, Hunmanby YO14 0PH
TELEPHONE +44 (0) 1723 890099 **FACSIMILE** +44 (0) 1723 893303
EMAIL sales@deepseaplc.com **WEBSITE** www.deepseaplc.com

DEEP SEA ELECTRONICS INC USA
3230 Williams Avenue, Rockford, IL 61101-2668 USA
TELEPHONE +1 (815) 316 8706 **FACSIMILE** +1 (815) 316 8708
EMAIL sales@deepseausa.com **WEBSITE** www.deepseausa.com

Deep Sea Electronics Plc maintains a policy of continuous development and reserves the right to change the details shown on this data sheet without prior notice. The contents are intended for guidance only.

Registered in England & Wales No.01319649
VAT No.316923457

DSEGenset®

DSE6110/20 MKII

AUTO START & AUTO MAINS FAILURE CONTROL MODULES

The DSE6110 MKII Auto Start Control Module and the DSE6120 MKII Auto Mains (Utility) Failure Control Module are suitable for a wide variety of single gen-set applications.

Monitoring engine speed, oil pressure, coolant temperature, frequency, voltage, current, power and fuel level, the modules give comprehensive engine and alternator protection. This is indicated on a large back-lit LCD text display via an array of warning, electrical trip and shutdown alarms in multiple languages.

Electronic J1939 (CAN) and non-electronic MPU and alternator sensing engine support for diesel, gas and petrol engines all in one variant. With a number of flexible inputs, outputs and protections, the modules can be easily adapted to suit a wide range of applications.

Through USB Communication both modules can be configured using the DSE Configuration Suite PC Software or through the module's front panel editor.

Using the DSE Configuration Suite PC Software the controller is easy to use and configure which allows alteration of operating parameters, sequences, timers and alarms.

AVAILABLE VARIANTS

6110-03	Auto Start with real time clock
6120-03	Auto Mains Failure with real time clock

ENVIRONMENTAL TESTING STANDARDS

ELECTRO-MAGNETIC COMPATIBILITY
BS EN 61000-6-2
EMC Generic Immunity Standard for the Industrial Environment
BS EN 61000-6-4
EMC Generic Emission Standard for the Industrial Environment

ELECTRICAL SAFETY
BS EN 60950
Safety of Information Technology Equipment, including Electrical Business Equipment

TEMPERATURE
BS EN 60068-2-1
Ab/Ae Cold Test -30 ºC
BS EN 60068-2-2
Bb/Be Dry Heat +70 ºC

VIBRATION
BS EN 60068-2-6
Ten sweeps in each of three major axes
5 Hz to 8 Hz at +/-7.5 mm,
8 Hz to 500 Hz at 2 GN

HUMIDITY
BS EN 60068-2-30
Db Damp Heat Cyclic 20/55 ºC at 95% RH 48 Hours
BS EN 60068-2-78
Cab Damp Heat Static 40 ºC at 93% RH 48 Hours

SHOCK
BS EN 60068-2-27
Three shocks in each of three major axes
15 GN in 11 mS

DEGREES OF PROTECTION PROVIDED BY ENCLOSURES
BS EN 60529
IP65 - Front of module when installed into the control panel with the optional sealing gasket.

COMPREHENSIVE FEATURE LIST TO SUIT A WIDE VARIETY OF GEN-SET APPLICATIONS